



THERMAL EXPANSION VALVE (BLOCK)



ALL APPLICATIONS

PROBLEM THERMAL EXPANSION VALVE MALFUNCTION

IMPROPER PERFORMANCE OF THE AC SYSTEM > DAMAGES OF OTHER SYSTEM COMPONENTS (AC COMPRESSOR)

The TXV is an advanced and fragile device. As it operates under high pressures and is temperature sensitive, improper working conditions as well as impurities inside the loop can cause its deregulation and malfunction.

If the expansion valve is stuck open or clogged, the AC system will not cool properly. A clogged valve will lead to too little refrigerant, increasing the pressure in the system and causing the AC compressor to overheat. If the valve is stuck open, too much refrigerant is allowed to pass through the system and into the compressor.



If the expansion valve fails, it can cause problems with the functionality and performance of the AC system - and if ignored, worst case scenario is expensive and irreversible damages of other system components such as the AC compressor.

BACKGROUND The vehicle's AC system operation relies on 2 factors: flow of refrigerant throughout the AC loop and the refrigerant's change of state. One of the key components allowing the AC system to work properly is the expansion control device. One of the commonly used designs in the automotive is a thermal expansion valve (TXV), which is usually installed at the evaporator inlet. Its main function is to convert liquid refrigerant into cold low-pressure gas and to regulate the flow of refrigerant through the vehicle's AC system.

The TXV meters refrigerant flow according to evaporator temperature and the load and cooling demand of the AC system. Inside the valve, a moveable rod enables the valve to open and close a passage, allowing refrigerant to move inside the valve. It accurately meters the precise amount of refrigerant needed according to outside temperature and need for air conditioning.

RECOMMENDED SOLUTION When suspecting malfunction of the expansion valve operation, it is recommended to perform an extended system diagnostics. Troubleshooting the system operating pressures by means of pressure gauges may reveal the most common issues with the expansion valve.

We recommend to follow a separate instruction to perform such diagnostics. Please consult Nissens' System Operating Pressures (R134A) poster.

If a failure on the valve is concluded, the part should be replaced.

Symptoms of a failing expansion valve - *continues on the next page >>*



The material and its contents are provided without warranty of any kind, and by publishing it, we disclaim any liability. Always follow the given vehicle manufacturer's instructions to comply with the right service and maintenance procedures. Nissens Automotive A/S shall not be held responsible for any property damage or personal injury, direct or indirect damage, due to failure or down time in vehicle operation caused by incorrect application, installation and/or abuse of our products.

©Nissens Automotive A/S, Ormhøjgårdvej 9, 8700 Horsens, Denmark. For further technical and contact information visit www.nissens.com

Nissens
Training
Concept



Nissens
DELIVERING THE DIFFERENCE



SYMPTOMS OF A FAILING EXPANSION VALVE

Poor AC System Performance or Warm Air

AC system underperformance may be a sign of a problem with the AC expansion valve. If the component fails or has an issue, it can disturb the performance of the AC system, causing it to underperform. The AC system may begin to blow noticeably less cold than before and may even begin to blow warm air depending on the severity of the problem.

Frost on AC Evaporator or Vents

Another symptom of a potential problem with the vehicle's expansion valve is frost coming from the vehicle's vents. AC evaporator malfunction can cause refrigerant to flow unmetered through the vehicle's AC system, causing the evaporator to freeze over or frost to come from the vehicle's AC vents. Either symptom is a sign that the system is getting too much refrigerant, ultimately lowering its efficiency and performance.

Inconsistent Air Flow




Sometimes a bad expansion valve will provide an inconsistent performance in its ability to regulate the flow of refrigerant throughout the system. If this occurs, the air coming out of the vent may be too cold or too warm. The air will likely alternate back and forth between different temperatures at various times. If the air varies between cold and warm, the expansion valve should be inspected at once.

Excessive Temperatures Generated at some of the Loop Components

A faulty or blocked expansion device will cause the system to operate under improper pressures, thus generate excessive temperatures. To diagnose possible failure, inspect the high-pressure side from the condenser outlet and to the expansion valve. Temperatures above 50°C within this sector warn about potential blockages/malfunctions of the expansion valve.

Improper System Operating Pressures

Too high or too low pressure gauge readings may be a sign of expansion valve malfunction. Normal gauge readings should be between 2 and 3 bar on the low side and 14 to 24 bar on the high side.




Low pressure:
Normal or too low




High pressure:
Too low

ONE OF POSSIBLE SYMPTOMS OF A FAULTY EXPANSION VALVE IS IMPROPER OPERATING PRESSURES READ ON GAUGES.



Impurities and debris concentration inside the TXV. System contamination, additives, worn receiver-dryer, particle formation after AC compressor seizure, improper flushing - all these may lead to inner blockages of the valve.



Severe AC compressor failure > seizure. Impaired lubrication caused by overheating, lubricant dilution or excessive impurities formation. All can be linked with a faulty TXV.

